



CATEGORY 6 F/UTP 4 PAIR 23 AWG CABLE

Norden Category 6 F/UTP cables exceed Category 6 / Class E specification. It is tested to 250 MHz frequency range and designed to support Gigabit 1000Base-T and 1000Base-Tx applications up to 100m.

Extremely high pair-balance providing excellent EMC (Electro Magnetic Compatibility), minimizing radiation, maximizing noise immunity and providing high alien cross talk performance to F/UTP (Foiled Twisted Pair) cabling systems. F/UTP (Twisted Pair – overall Foil shield) cabling systems are installed for improved Alien Cross talk performance.



COMPLIANCE

ANSI/TIA-568-C.2:2009 Category 6
 ISO/IEC-11801, Class E
 IEC 61156-5: 2002 Category 6
 LSZH: IEC 60332-1, IEC 60754, IEC 61034
CPR Compliance to Eca
 EN 60332-1-2

PRODUCT CLASSIFICATION

Product Sequence	Euro Class
Product Type	Twisted Pair Cable

MATERIAL CONSTRUCTION & DESIGN

Conductor Material	Bare Copper
Conductor Size	23 AWG
Conductor Construction	Solid
Insulation Material	High Density PE
Insulation Diameter	1.09 mm norm.
Conductor Unit Identification	Solid/Stripe
Drain Wire	Tinned Copper 0.41 mm
Overall Shield	Laminated Aluminium foil (foil face in) ,100 % coverage
Outer Jacket	LSZH Low Smoke Zero Halogen
Outer jacket Thickness & Ex. Diameter	0.60±0.05 mm, 7.4±0.4 mm
Colour Code	Per TIA/EIA 568-B
Total Number of Wires	8
Rip Cord	Yes
Outer Jacket Colour	Per Requirement
Marking	Per Requirement

CATEGORY 6 F/UTP 4 PAIR 23 AWG CABLE

ELECTRICAL & MECHANICAL CHARACTERISTICS

Frequency Range	1 - 250 MHz
Impedance	100 Ω ±15
Coupling Attenuation	40 dB min @ 30-100 MHz 40-20 Log (f/100) @100-300 MHz
DC Resistance	73 Ω/km norm.
Max. Resistance Unbalance	4 %
Capacitance	5.6 nF/100m max.
Capacitance Unbalance	3.3 pF/m max.
Propagation Delay Skew	35 ns/100m max.
Velocity of Propagation	69 %
Dielectric Strength	1 KV/minute
Min. Insulation Resistance	5 GΩ•km
Max. Tensile Strength - Short Term	110 N
Min. Bend Radius	53.6 mm
Operating Temperature Range	-10 °C +65 °C

TRANSMISSION PERFORMANCE

Freq. MHz	Attenuation dB/100m @ 20°C	NEXT dB	PSNEXT dB	RL dB	ELFEXT dB	PSELFEXT dB
1	2.0	80.0	78.0	27.0	81.8	77.8
4	3.8	75.0	72.8	30.0	76.8	73.8
10	6.0	71.0	69.0	30.0	70.0	67.8
20	8.5	62	60.2	30.0	58.8	55.8
31.25	10.4	60.9	58.9	28.6	56.8	53.3
100	19.8	54.0	52.0	26.0	47.8	44.8
150	24.7	50.7	48.7	25.1	43.3	40.3
200	29.0	48.1	46.1	23.8	38.8	35.8
250	32.8	46.3	44.3	22.0	36.8	33.8

*Supplied cables meets Cat. 6 min. transmission requirements as per IEC 61156-5 Ed. 2

ORDERING INFORMATION

Part Number	Description	Standard Length
113-1000E204PL	Category 6 F/UTP 4 Pair 23 AWG Cable LSZH CPR-Eca Purple	305 mtr

X: BK(Black), BL(Blue), GN(Green), GY(Gray), RD(Red), WH(White), YL(Yellow), PL(Purple)

PACKING INFORMATION

Part Number	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
113-1000E204PL	Plywood Reel/Ctn	16.25	18.45	390 x 390 x 281