


2MP MOTORIZED VANDAL DOME CAMERA



ENC-HVD5M-40R-69

FEATURES

- 2.7 ~ 13.5 mm Motorized Lens
- Smart IR up to 40 m (Upgradable to 50 m)
- ONVIF Profile (S, G, T)
- Triple Stream
- Audio and Alarm Support
- PoE, IK10, IP67



SPECIFICATION

MODEL		Model No.	ENC-HVD5M-40R-69
CAMERA		Type	2MP MOTORIZED VANDAL DOME CAMERA
		Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
		Day/Night	IR Cut Filter with Auto Switch
		Lens Type	Motorized
		Focal Length	2.7 ~ 13.5 mm
		Digital Zoom	16x
		Focus	Auto / Manual
		Iris	Fixed Iris
		Angle of View (H)	101.0° ~ 28.0°
		Angle of View (V)	54.0° ~ 16.0°
		Angle of View (D)	114.0° ~ 32.2°
		Angle Adjustment	Pan 0~355°, Tilt 0~75°, Rotate 0~355°
		Shutter	1s ~ 1/100,000s, Auto / Manual
		Min. Illumination	Color: 0.001 lux @ F1.6, B/W: 0 lux with IR
		AGC	Auto / Manual
		Digital Noise Reduction	2D & 3D DNR, Auto / Manual
S/N Ratio	≥55 dB		
Defog	Smart Defog		
WDR	120 dB		
Smart IR	Up to 40 m (Upgradable to 50 m)		
Wavelength	850 nm		

★Product specification and availability are subject to change without notice.

2MP MOTORIZED VANDAL DOME CAMERA



ENC-HVD5M-40R-69

MODEL	Model No.	ENC-HVD5M-40R-69
	Type	2MP MOTORIZED VANDAL DOME CAMERA
DORI	Lens	2.8 ~ 13.5 mm
	Detection	48 ~ 152 m
	Observation	19.2 ~ 60.8 m
	Recognition	9.6 ~ 30.4 m
	Identification	4.8 ~ 15.2 m
VIDEO	Max. Resolution	1920x1080
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x720) @ 25/30fps Sub Stream: (704x576, 640x480, 640x360, 352x288, 320x240) @ 25/30fps Third Stream: (640x480, 352x288, 320x240) @ 25/30fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 12 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night (Color, Mono, Auto), Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711A, G.711U, RAW_PCM
	Audio Bit Rate	64 kbps, 128 kbps
	Audio I/O	1/1
	Built-in Mic	Supported
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Multi Loitering, Abandoned Object (Object Left), Missing Object (Object Lost)
	Statistical Analysis	Face Detection, People Counting, Human & Vehicle Detection, Abnormal Audio Detection, Wrong Way Detection, Illegal Parking, Tampering / Masking / Scene Change, Abnormal Speed
	Alarm Management	Motion Detection, Tampering (Masking), Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Abnormal Audio Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
	Alarm Notifications	E-mail (Notification and Snapshot), HTTP (Alarm Icon), FTP (Snapshot and Recording), SD Card (Recording)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, 802.1X, Unicast, Multicast, QoS, ARP, SNMP, Telnet, SSL/TLS1.2, RTMP (Optional)
	Security	TLS Video Encryption, IP Filter, User Authentication (Multiple Privilege Level), 802.1X Authentication (EAP-MD5), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF Profile (S, G, T), SDK/CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	1/1
	Edge Storage	SD card slot, up to 512 GB
	ANR	Supported
	Max User	32
GENERAL	Client Application	EyeGuard
	Power Supply	12V DC, PoE (IEEE 802.3af)
	Max. Power Consumption	≤7.5 W
	Working Temperature	-40 °C ~ 65 °C
	Working Humidity	≤95% RH (non-condensing)
	Ingress Protection	IP67
	Vandal Resistant	IK10
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	Φ130x113.3 mm
Net Weight	0.8 Kg	


★Product specification and availability are subject to change without notice.

2MP MOTORIZED VANDAL DOME CAMERA



ENC-HVD5M-40R-69

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HVD5M-40R-69	2MP H.265 IR IP Vandal Proof Dome Camera with 2.7 to 13.5mm Motorized Lens, WDR, PoE, SD Card Slot, Built in Mic (Optional) , Smart Analytics and 40m (Upgradable to 50m) IR Support	1
ENB-BCDJ67	Junction Box for Norden Dome Camera	1
ENB-BCDQ66	Pendent Cap for Norden Dome Camera	1
ENB-BCDP66	Pendant Mount for Norden Dome Camera	1
ENB-BCDW66	Wall Mount Bracket for Norden Dome Camera	1
ENB-BCDU66	Pole Mount Bracket for Norden Dome / Mini PTZ Camera	1
ENB-BCPH65	Corner Mount Bracket for Dome / Mini PTZ Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HVD5M-40R-69	Carton Box	-	-