32CH EMBEDDED NETWORK VIDEO RECORDER **EYENOR**®





ENR-04032-N-GK

FEATURES

32 Channel Input Support H.265+, H.265, H.264 Video Formats 4 SATA HDDs HDMI and VGA Simultaneous Output Support RAID (0/1/5/6/10) ONVIF Profile (S, G, T)





















SPECIFICATION

MODEL	Model No.	ENR-04032-N-GK
№	Туре	32CH EMBEDDED NETWORK VIDEO RECORDER
VIDEO & AUDIO	Video Input	32-Ch
	Incoming Bandwidth	320 Mbps
	Outgoing Bandwidth	320 Mbps
	HDMI / VGA Output	HDMI 2: 3840×2160,1920×1080, 1440×900, 1280×1024 VGA /HDMI 1: 1920×1080,1440×900, 1280×1024
	Audio Input / Output	1/1
	Two-way Audio	Supported
	Multi-screen Display	1st Screen: 1/4/8/9/16/32/36 2nd Screen: 1/4/8/9/16
	Video Encryption	Supported
	OSD	Channel Name, Date
	Video Compression	H.265+, H.265, H.264
	Audio Compression	G.711U, G.711A
<u> </u>	Video Bit Rate	CBR,VBR
DECODING	Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/D1
	Recording Mode	Continuous, Manual, Event(Pre/Post, Motion etc.), Schedule
	Trigger Events	Motion Detection, Video Loss, Alarm in, IVS
	Decoding Capability	1x12MP, 4x8MP, 8x4MP, 16x1080P, 32x720P
	Fisheye Camera	Supported
	De-warping	Supported

32CH EMBEDDED NETWORK VIDEO RECORDER **EYENOR**°



ENR-04032-N-GK

귝	Model No.	ENR-04032-N-GK		
MODEL	Туре	32CH EMBEDDED NETWORK VIDEO RECORDER		
	Synchronous Playback	16/9/4/1		
MONITORING	Live View Functions	Snapshot, Record, Digital Zoom, Record, PTZ toolbar, Volume adjustment, Image Setting		
	Playback functions	Sync playback, Play, Pause, Stop, Fast play, Slow play, Full Screen, Backup selection, Snapshot, Search by events, Picture grid		
	Search Mode	Time/Date, Alarm, Picture grid, Event		
Σ	Backup Mode	USB, Network, e-SATA		
	Export Video Format	MP4		
щ	Protocols	TCP/IP, UDP, IPv4, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, FTP, UPnP, SMTP, SNMP, P2P, IP Filter, 802.1X, 3G/4G		
ĕ	Compatibility	ONVIF Profile (S, G, T), SDK/CGI		
INTERFACE	Network	2xRJ45 (10/100/1000 Mbps) Self Adaptive Ethernet Port		
	Serial Interface	1xRS485 & 1xRS232		
	USB Interface	2xUSB 2.0, 1xUSB 3.0		
	Alarm Interface	16 Input / 4 Output		
	Analytics	Face Comparison, Human Detection, Vehicle Detection, Non-Motor Vehicle Detection,		
-	Intelligent Search	Gender, Pictures, Time, Properties, Vehicle Color, Cycling Style		
SMART	Alarm Management	Alarm Push & Prompt, e-mail, Alarm Out, Immediate Comparison of Result		
SM	Face Recognition	Max 20 Face Pictures/ sec, Strange Face Detection, Intelligent Search, Support up to 16 Face Database, Total 9,000 Face Images		
	Body Temperature Detection	Real Time Temperature Display, Intelligent Search (Time, Temperature Type, Person Type, ID), Max. 20 Face Pictures/ sec		
	SATA	4 SATA Interfaces		
ш	Capacity	Up to 12 TB for each HDD		
AG	Array Type	RAID 0/1/5/6/10		
STORAGE	e-SATA	Supported		
ST	ANR	Supported		
	Cloud Storage	Supported		
	Operating System	Embedded Linux		
	Remote Users	8		
	Web Client	Eye Guard		
7	Power	AC100 ~ 240V		
E	Redundant Power	N/A		
GENERAL	Power Consumption (without HDD)	≤15 W		
G	Working Environment	-10 °C ~ 50 °C		
	Humidity	< 90% RH		
	Dimension	440x368.3x70 mm		
	Net Weight	4.5 kg		

Dimension Unit: mm





ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-04032-N-GK	32Ch Embedded Network Video Recorder with 4 HDD Bays Supports 4K Cameras, Face Recognition, Body Temperature Measurement , HDMI, VGA and ONVIF	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-04032-N-GK	Carton Box	-	-