

32CH NETWORK VIDEO RECORDER



ENR-04032-N-FRK

FEATURES

- 32 Channel input
- Support Enhanced (H.265, H.264), H.265, H.264 Video Formats
- 4 SATA HDDs
- HDMI and VGA simultaneous output
- Support RAID (0/1/5/6/10)
- eSATA Interface
- ONVIF Profile S



SPECIFICATION

| | | |
|--------------------------|--|---|
| MODEL | Model No. | ENR-04032-N-FRK |
| | Type | 32CH NETWORK VIDEO RECORDER |
| VIDEO & AUDIO | Video Input | 32-Ch |
| | Incoming Bandwidth | 320Mbps |
| | Outgoing Bandwidth | 320Mbps |
| | HDMI/VGA Output | HDMI 1: 3840x2160, 1920x1080, 1280x1024, 1024x768 HDMI 2 / VGA: 1920x1080, 1280x1024, 1024x768 |
| | Audio I/O | 1-ch Input/ 1-ch Output |
| | Two way Audio | Supported |
| | Multi-screen Display | 1st Screen: 1/4/8/9/16/32 2nd Screen: 1/4/8/9/16 |
| | OSD Type | Channel Name, Date |
| DECODING | Video Compression | Enhanced (H.265, H.264), H.265, H.264 |
| | Audio Compression | G.711A/G.711U |
| | Bit Rate Type | CBR, VBR |
| | Recording Resolution | 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 |
| | Recording Mode | Manual, Schedule (Regular, Continuous), Event |
| | Trigger Events | Motion Detection, Video Loss, Alarm in, IVS |
| | Simultaneous Live Decoding Capability | 1x12MP, 4x8MP, 9x1080P, 16x1080P |
| MONITORING | Synchronous Playback | 16/9/4/1 |
| | Live View Functions | Snapshot, Record, Digital Zoom, Record, PTZ toolbar, Volume adjustment, Image Setting |
| | Playback functions | Sync playback, Play, Pause, Stop, Fast play, Slow play, Full Screen, Backup selection, Snapshot, Search by events, Picture grid |
| | Search Mode | Time/Date, Alarm, Picture grid, Event |
| | Backup Mode | USB, Network, eSATA |
| | Export Picture Format | MP4 |

★Product specification and availability are subject to change without notice.



32CH NETWORK VIDEO RECORDER



ENR-04032-N-FRK

| | | |
|------------------|------------------------|---|
| MODEL | Model No. | ENR-04032-N-FRK |
| | Type | 32CH NETWORK VIDEO RECORDER |
| INTERFACE | Protocols | TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTSP/RTCP, PPPoE, NTP, UPnP, QoS, SMTP, IGMP, 802.1X, NFS, Unicast, Multicast, ARP, SNMP, SSL, Telnet, SFTP (SSH), P2P, 3G/4G |
| | Compatibility | ONVIF Profile S, SDK / CGI |
| | Network | 2xRJ45 (10/100/1000 Mbps) Self Adaptive Ethernet Port |
| | Serial Interface | 1xRS485, 1xRS232 |
| | USB Interface | 2xUSB 2.0, 1xUSB 3.0 |
| | Alarm I/O | 16/4 |
| SMART | Alarm Management | Input & Output Event, Alarm I/O Error, IP Conflict, Hard Disk Full, No Hard Disk, Hard Disk R/W Error, HDD SMART Check Error, Abnormal Recording, Hot Spare Error & Array Error, Motion Detection, Tampering (Masking), Smart detection, Video loss |
| | Behavior Detection | Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire) |
| | Analytics | Loitering, Multi Loitering, Abandoned object (Object Left), Missing object (Object Lost), People Counting, Wrong Way Detection, Abnormal Speed, Illegal Parking *Compatible with analytic supported cameras |
| STORAGE | SATA | 4 SATA Interfaces |
| | Capacity | Up to 16TB for each HDD |
| | Array Type | RAID 0/1/5/6/10 |
| | eSATA | Supported |
| | ANR | Supported |
| GENERAL | Operating System | Embedded Linux |
| | Remote Users | 8 |
| | Client Application | EyeGuard |
| | Power Supply | 100 ~ 240V AC |
| | Redundant Power | N/A |
| | Max. Power Consumption | ≤15W (without HDD) |
| | Working Environment | -10°C ~ 55°C |
| | Working Humidity | ≤90% RH |
| | Chassis | 1.5U |
| | Dimension | 440 × 368.3 × 70 mm |
| Net Weight | 4.65 kg (without HDD) | |

Dimension Unit : mm



ORDERING INFORMATION

| Part Number | Description | Standard Quantity |
|-----------------|--|-------------------|
| ENR-04032-N-FRK | 32 Ch Embedded Network Video Recorder with 4 HDD Bays Supports 4K Cameras, HDMI, VGA and ONVIF | 1 |

PACKING INFORMATION

| Part Number | Packing Mode | Gross weight(Kg) | Dimension(mm) |
|-----------------|--------------|------------------|---------------|
| ENR-04032-N-FRK | Carton Box | - | - |

★Product specification and availability are subject to change without notice.