

8MP MULTI SENSOR PANORAMIC PTZ CAMERA **EYENOR**[®]

ENC-HHPAQ-500L-96

FEATURES

Starlight Illumination

44X Optical Zoom

16X digital Zoom

Laser IR, Up to 500 m

ONVIF Profile (S, G, T)

Triple Streams

Built-in Speaker

IP67



SPECIFICATION

MODEL	Model No.	ENC-HHPAQ-500L-96
	Type	8MP MULTI SENSOR PANORAMIC PTZ CAMERA
PANORAMIC CAMERA	Image sensor	4x1/1.8" CMOS Progressive 2.0 MegaPixel
	Lens Type	Fixed
	Focus	Fixed
	Focal Length	5 mm
	Aperture	F2.2
	Angle of View (H)	180°
	Angle of View (V)	74°
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.01 lux @ F2.2
	AGC	Auto / Manual
Max. Resolution	4096x1800	
Main Stream	(4096x1800, 3840x1680, 2720x1192) @ 25/30fps	
Sub Stream	(704x320) @ 25/30fps	
Third Stream	(1280x560) @ 25/30fps	

8MP MULTI SENSOR PANORAMIC PTZ CAMERA



ENC-HHPAQ-500L-96

MODEL	Model No.	ENC-HHPAQ-500L-96
	Type	8MP MULTI SENSOR PANORAMIC PTZ CAMERA
PTZ CAMERA	Image sensor	1/1.8" CMOS Progressive 2.0 MegaPixel
	Day / Night	IR Cut Filter with Auto Switch
	Lens Type	Motorized Zoom Lens
	Focus	Auto / Semi Auto / Manual
	Focal Length	5mm ~ 220mm (6mm ~ 264mm) Lens
	Optical zoom	44X
	Digital Zoom	16X
	Zoom Speed	<5s
	Iris	DC Auto Iris
	Aperture	F1.5 ~ F4.8
	Angle of View	61.2° ~2.0°
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. illumination	Color: 0.0008 lux @ F1.5
	AGC	Auto / Manual
	Digital Noise Reduction	3D DNR
	S/N Ratio	>55 dB
	Defog	Smart Defog
WDR	140 dB	
Laser IR	Up to 500 m	
White LEDs	4	
White Light Distance	50 m	
VIDEO & AUDIO	Max. Resolution	1920x1080
	Video Compression	H.265+, H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x960, 1280x720) @ 50/60fps Sub Stream: (704x480, 704x240, 352x240) @ 30fps, (704x576, 704x288, 352x288) @ 25fps Third Stream: (1920x1080, 1280x960, 1280x720, 640x480, 704x480, 352x240) @ 30fps, (1920x1080, 1280x960, 1280x720, 640x480, 704x576, 352x288) @ 25fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate, EIS, SVC
	Video Bit Rate	32 kbps ~ 16 Mbps
	Bitrate Type	CBR, VBR
	Image Setting	Brightness, Contrast, Saturation, Hue, Sharpness, Rotation/Mirror, Gain, Exposure, Day/Night
	White Balance	Auto, Semi Auto, Sunshine, Daylight, Warm Light, Filament, Nature Light, Lock WB, Manual
	HLC	Supported
	BLC	Supported
	OSD	Total 5 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes (16x16, 24x24, 32x32, 48x48, 64x64, 96x96), Image overlay
	ROI	Up to 7 regions
	Privacy Mask	Up to 24 regions
Heatmap	Supported	
AUDIO	Audio Compression	G.711A, G.711U, ADPCM_D, AAC_LC
	Audio Bit Rate	8 kbps ~ 48 kbps
	Audio I/O	1/1
	Two-Way Audio	Supported
	Audio Voltage	Audio Cable; Input: Impedance 35 kΩ, Amplitude 2 V [p-p]
	Built-in Mic	N/A
SMART	Behaviour Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Running, Abandoned Object (Object Left), Missing Object (Object Lost), Parking
	Statistical Analysis	Face Detection , People Counting, Crowd Detection, On Duty Detection, Helmet Detection, Human & Vehicle Classification, Abnormal Video & Audio Detection, Early Warning
	Alarm Management	Motion Detection, Tampering (Masking), , IP Address Conflict, Pre/Post Alarm Recording, Alarm Recording/Snapshot, Harsh Voice Alarm
	Auto Tracking	Supported


8MP MULTI SENSOR PANORAMIC PTZ CAMERA



ENC-HHPAQ-500L-96

MODEL		ENC-HHPAQ-500L-96
Type		8MP MULTI SENSOR PANORAMIC PTZ CAMERA
Protocols		TCP/IP, IPv4, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTSP, PPPoE, NTP, UPnP, SMTP(SSL/TLS), IGMP, QoS (DSCP), Unicast, Multicast, P2P
Security		AES Video Encryption, IP Filter, User authentication (multiple privilege level), 802.1X authentication (EAP-MD5), Digest authentication, User Access Log
Compatibility		ONVIF Profile (S, G, T), SDK/API/CGI
Network		1 x RJ45 10M/100M/1000M Self Adaptive Ethernet Port
Alarm Interface		8 Input / 2 Output
Alarm Voltage		Output: Impedance 600 Ω, Amplitude 2 V [p-p]
Serial Interface		1xRS485
BNC		Supported
USB		N/A
Edge Storage		Micro SD card slot, up to 128 GB
ANR		Supported
Built-in Speaker		Supported
Built-in Heater		Supported (Optional)
Cable Interface		Pigtail
Remote Connection		≤7
Web Client		EyeConnect
Web Language		11
Wiper		N/A
Pan Range		360°
Pan Speed		Pan Manual Speed: 0.1°~200°/s, Pan Preset Speed: 240°/s
Tilt Range		-16° ~ +90° (auto flip)
Tilt Speed		Tilt Manual Speed: 0.1°~120°/s, Tilt Preset Speed: 160°/s
Number of Presets		500
Preset Accuracy		±0.3°
Patrol		16, up to 32 presets per cruise
Scan		8
Pattern		8, each with 600s memory or 1000 orders
Power-off Recovery		Supported
Power		AC24V
Max. Power consumption		85W (IR OFF), 110W (IR ON)
Working Temperature		-30 °C ~ 65 °C
Working Humidity		0-95% RH (non-condensing)
Ingress Protection		IP67
Vandal Resistant		IK10 (Housing)
Surge Protection		TVS6000V
Reset Button		Supported
Dimension		Φ358×568 mm
Weight		17 Kg

Dimension Unit : mm



8MP MULTI SENSOR PANORAMIC PTZ CAMERA

ENC-HHPAQ-500L-96

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HHPAQ-500L-96	8MP Starlight IR IP H.265 High Speed Multi Sensor Panoramic PTZ Dome Camera with 44X Optical Zoom, SD Card Slot, WDR, Smart Analytics, Built-in Speaker and 500m Laser IR Support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HHPAQ-500L-96	Carton Box	25	550×470×730