


8CH MOBILE NVR



ENR-21008-N-RK

FEATURES

- _____ H.265 Compression
- _____ 9-36V Wide Voltage
- _____ Real Time Monitoring
- _____ SD Card Storage up to 512 GB
- _____ Support GPS, Wi-Fi, 4G



SPECIFICATION

MODEL	Model No.	ENR-21008-N-RK
	Type	8CH MOBILE NVR
VIDEO & AUDIO	Image Resolution	8x1080P (1920x1080)
	Video Compression	H.265, H.264
	Video Input	8Ch IPC 1080P Input
	VGA Output	1Ch, support 1920x1080, 1280x720, 1024x768
	CVBS Output	1Ch Aviation Output PAL/NTSC, 1.0Vp-p, 75Ω
	Video display	Single Ch / Four Ch / Nine Ch
	Video Standard	PAL / NTSC: 25/30fps
	System Resource	PAL / NTSC: 200/240fps
	Playback Resolution	1- 8CH x 1080p
	Image Quality	1-14 Levels Adjustable
	Video Bit-Rate	192 kbps ~ 4 Mbps (per channel)
	Video Space Requirement	85 ~ 3600 MByte/hour
	Record Format	Synchronized Video & Audio
	Audio compression	G.711A / G.711U
Audio Bit-Rate	4K Byte/s (per channel)	
INTERFACE	Compatibility	ONVIF
	Security	AES Encryption, Password Protection
	Network	1 x RJ45 10M/100M/1000M Self Adaptive Ethernet Port
	Serial Interface	3xRS232, 2xRS485
	Wi-Fi	Built-in Wi-Fi module 2.4GHz/5.8GHz (IEEE802.11 n/g/b)
	USB	1xUSB 3.0, 1xUSB 2.0
	GPS	Supported
	SIM Slot	2 x 3G/4G
	Intercom	1xMIC Input
	G-Sensor	Built-in G-Sensor
	Audio I/O	8/1
	Alarm I/O	12/3
	SD Card	Micro SD card slot, Support up to 512 GB
	HDD	2 x 2.5" SATA HDD(2*7mm or 1*15mm thick), max 4TB
eSATA port	Supported	

★Product specification and availability are subject to change without notice.

8CH MOBILE NVR



ENR-21008-N-RK

MODEL	Model No.	ENR-21008-N-RK
	Type	8CH MOBILE NVR
GENERAL	OS	LINUX
	Operation Interface	Graphical Menu Operation Interface (OSD Menu)
	Power	DC9-36V
	Max. Power Consumption	≤12W PoE
	Working Temperature	-40 °C ~70 °C
	Working Humidity	≤80%
	Dimensions	235x190x80 mm
	Weight	3.0kg (without HDD)

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-21008-N-RK	8Ch Mobile NVR with 2 HDD Bay, 1 SD Card Slot, GPS, Wi-Fi and 4G Support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-21008-N-RK	Carton Box	-	-