

# 2MP IR IP VEHICLE DOME CAMERA



## ENC-HTC5F-20R-16

### FEATURES

2MP Resolution

Mini Size Dome Camera for Vehicle

3.6 mm Fixed Lens

Smart IR up to 20 m

IP66



### SPECIFICATION

<b>MODEL</b>	Model No.	<b>ENC-HTC5F-20R-16</b>
	Type	2MP IR IP VEHICLE DOME CAMERA
<b>CAMERA</b>	Image Sensor	1/2.9" CMOS
	Day / Night	Auto / Color / Black & White
	Lens	3.6 mm
	Angle Adjustment	Bracket- Pan: 0~355°, Tilt: 0~90°, Rotate: 0~355°
	Shutter	1/25s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.01 lux @ F1.2, 0 lux with IR
	AGC	Auto / Manual
	S/N Ratio	≥52 dB
	WDR	Digital WDR
	Smart IR	Up to 20 m
<b>VIDEO</b>	Max.Resolution	1920x1080
	Video Compression	H.265,H.264
	Frame Rate	Main stream: 1920x1080 @ 25/30fps Sub Stream: 720x576 @ 25/30fps
	Video Bit Rate	128 kbps ~ 8 Mbps
Synchronization system	Inter-sync	
<b>INTERFACE</b>	Protocol	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPOE, NTP, NFS, UpnP, IGMP, SMTP, 802.1x, QoS, ARP, SNMP, SSL, SFTP
	Compatibility	ONVIF
	Network	RJ45 Connector
	BNC	N/A
<b>GENERAL</b>	Power	12V DC
	Power consumption	<5W
	Working Temperature	-10 °C ~ 60 °C
	Working Humidity	≤90% (no condensation)
	Ingress protection	IP66
	Dimensions	93x67 mm
Weight	0.310 kg	

★Product specification and availability are subject to change without notice.

# 2MP IR IP VEHICLE DOME CAMERA



**ENC-HTC5F-20R-16**

## ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HTC5F-20R-16	2MP H.265 IR IP Vehicle Dome Camera with 20m IR, Power from MNVR – RJ45 Connector	1

## PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HTC5F-20R-16	Carton Box	-	-