

# Wall Mount Speaker 6W



Wall Mount Speaker

## DESCRIPTION

NVS-L1003006WS is an economic Wall mount speaker made of plastic enclosure. This speaker have 100V built-in transformer and 5" driver unit that delivers 6W/8 Ohm power output. The 100V transmission is realized in a high-voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple speakers possible. It is suitable for Schools, Offices, Supermarkets etc.

## FEATURES

- ◉ Nickel-plated brass connection terminals
- ◉ Multi-chambered enclosure design
- ◉ Wide Frequency Response
- ◉ High Quality ABS Plastic body
- ◉ Environmentally resistant hardware

Specifications	
Model	NVS-L1003006WS
Material	ABS Plastic
Rated Power	6W
Driver Unit	5"x 1
Input Voltage	100V
Impedance	80hms
Power tapping	3/6W
Sensitivity (1m, 1w)	92dB ±2dB
Transformer tapings	6W(100V)
Maximum SPL(@ 1W/m)	99dB
Frequency Response	130Hz -16KHz
Coverage angle(HxV)	165°x90°
Input Connector	Push in terminal
Operating temperature	-25°C~+55°C
Weight	0.85kg
Dimension H×W×D(mm)	185x228x85mm

**NVS-L1003006WS**



# Wall Mount Speaker 6W

## ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-L1003006WS	Wall Mount Speaker 6W	01

## ACCESSORIES INFORMATION

Description	Standard Quantity
User Manual	01