


# 8CH AHD MOBILE DVR



## ENR-11008-N-SD

### FEATURES

- H.265 Compression
- 8-36V Wide Voltage
- Real Time Monitoring
- SD Card Storage up to 256 GB
- Support GPS, Wi-Fi and 4G



### SPECIFICATION

MODEL	Model No.	ENR-11008-N-SD
	Type	8CH AHD MOBILE DVR
VIDEO & AUDIO	Image Resolution	8x1080P (1920x1080)
	Video Compression	H.265, H.264, MJPEG
	Streams	Dual Stream Independently Configurable
	Video Input	8Ch AHD 1080P Input
	VGA Output	1Ch, support 1920x1080, 1280x720, 1024x768
	CVBS Output	1Ch Aviation Output PAL/NTSC, 1.0Vp-p, 75Ω
	Video display	Single Ch / Four Ch
	Video Standard	PAL / NTSC : 25/30fps
	System Resource	PAL / NTSC : 100/120fps
	Playback Resolution	1- 8CH x 1080p
	Image Quality	1-14 Levels Adjustable
	Video Bit-Rate	192 kbps ~ 8 Mbps (per channel)
	Video Storage	85 ~ 3600M Byte/hour
	Record Format	Synchronized Video & Audio
Audio compression	G.711A / G.711U	
Audio Bit-Rate	4K Byte/s (per channel)	
Recording	Modes: Normal, Schedule based, Alarm, Motion detection, Video loss, Camera Cover, Vehicle Speed Event Based : Pre and Post Recording. Up to 1 ~330 s Configurable	
INTERFACE	Compatibility	ONVIF
	Security	AES Encryption, Password Protection
	Network	1xRJ45 (10M/100M/1000M) Self Adaptive Ethernet Port
	Serial Interface	1xRS232, 1xRS485 (Optional)
	Wi-Fi	Built-in Wi-Fi module 2.4GHz/5.8GHz (IEEE802.11 n/g/b)
	USB	1xUSB 2.0
	GPS	Supported
	SIM Slot	1 x 3G/4G
	Intercom	1xMIC Input Optional
	G-Sensor	Supported (Optional)
	Audio I/O	8/1
	Alarm I/O	4/2
Edge Storage	Micro SD card slot, Support up to 256GB	
HDD	1 x 2.5" SATA HDD(7mm thick), max 4TB	

★Product specification and availability are subject to change without notice.

# 8CH AHD MOBILE DVR



## ENR-11008-N-SD

MODEL	Model No.	ENR-11008-N-SD
	Type	8CH AHD MOBILE DVR
SMART	DSM	1Ch DSM Video Input Safety Alarm for Yawning, Calling, Smoking , Blocked & Device Malfunction
	ADAS / BSD	1Ch BSD Video Input Safety Alarm for Pedestrians, Non-Motorized Vehicles such as bicycles, motorcycles, electric bicycles, tricycles ( Front side / Back)
	Seat Belt Detection	Supported
	Motion Detection	Supported
GENERAL	OS	LINUX
	Operation Interface	Graphical Menu Operation Interface (OSD Menu)
	Notifications via Mail / SMS	Vehicle Speed, Vehicle Acceleration, Alarm Triggered, Video Loss, Camera Tamper, SSD Error
	Power	DC8-36V
	Max. Power Consumption	≤12W
	Working Temperature	-40 °C ~70 °C
	Working Humidity	≤80%
	Dimensions	170x128x56 mm
Weight	1.04 kg	

### ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-11008-N-SD	8Ch AHD Mobile DVR with 1 HDD Bay, 1 SD Card Slot, GPS , 4G, DSM, ADAS and BSD Support	1

### PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-11008-N-SD	Carton Box	-	-