

2MP VEHICLE PTZ CAMERA



ENC-HVP5Z-100R-16

FEATURES

25X Optical Zoom, 16X Digital Zoom

ONVIF Profile (S, G, T)

Triple Stream

IP67

Top Mounted on Vehicle



SPECIFICATION

MODEL	Model No.	ENC-HVP5Z-100R-16
CAMERA	Type	2MP VEHICLE PTZ CAMERA
	Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
	Day / Night	IR Cut Filter with Auto Switch
	Lens Type	Zoom Lens
	Focal Length	5mm ~ 125mm
	Focus	Auto / Semi Auto / Manual
	Iris Type	DC Auto Iris
	Angle of View (H)	58.50° ~ 2.8°
	Angle of View (V)	33.2° ~ 1.5°
	Angle of View (D)	67.2° ~ 3.1°
	Aperture Range	F1.6 ~ F3.67
	Optical Zoom	25X
	Digital Zoom	16X
	Shutter	1s-1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.07 lux @ F1.6, B/W:0.007 lux, 0 lux with IR on
	AGC	Auto / Manual
	Digital Noise Reduction	2D & 3D DNR, Auto/ Manual
	S/N Ratio	≥55 dB
	Defog	Smart Defog
WDR	120 dB	
Smart IR	Up to 100m	

★Product specification and availability are subject to change without notice.


2MP VEHICLE PTZ CAMERA



ENC-HVP5Z-100R-16

MODEL	Model No.	ENC-HVP5Z-100R-16
	Type	2MP VEHICLE PTZ CAMERA
VIDEO	Max. Resolution	1920x1080
	Video Compression	H.265+, H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x720) @ 25/30fps Sub Stream: (D1, VGA, 640x360, CIF, QVGA) @ 25/30fps Third Stream: (VGA, CIF, QVGA) @ 25/30fps
	Video Bit Rate	100 kbps ~ 12 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day / Night (Color, Mono, Auto)
	White Balance	Auto / Manual
	HLC	Supported
	BLC	Supported
	OSD	Supported
	ROI	Up to 8 regions
Privacy Mask	Up to 4 regions	
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTCP, RTSP, PPPoE, NTP, UPnP, SMTP (SSL/TLS), IGMP, 802.1X, Unicast, SNMP, ARP
	Security	IP Address Filtering, User Authentication (Multiple Privilege Level), 802.1X Authentication, HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF (S,G,T) CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Serial Interface	1xRS485
Edge Storage	SD card 256GB	
PAN AND TILT	Pan Range	0° ~ 360°
	Pan Speed	Pan Manual Speed: 0° ~ 220° /s Pan Preset Speed: 300° /s
	Tilt Range	-20° ~ 90°
	Tilt Speed	Tilt Manual Speed: 0°/s ~ 90°/s Tilt Preset Speed: 120°/s
	Preset Positioning	256
Cruise Track	8	
GENERAL	Power Supply	DC 12V
	Power Consumption	18W
	Working Temperature	-40 °C ~ +60 °C
	Working Humidity	≤80% RH (non-condensing)
	Ingress Protection	IP67
	Reset Button	Supported
	Dimensions	120x210x124 mm
Net Weight	2.5 kg	
Bracket	Optional	

Dimension Unit : mm



★Product specification and availability are subject to change without notice.

2MP VEHICLE PTZ CAMERA



ENC-HVP5Z-100R-16

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HVP5Z-100R-16	2MP IR IP H.265 Vehicle PTZ Camera with 25X Optical Zoom, SD Card slot and 100m IR Support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HVP5Z-100R-16	Carton Box	-	-