

IP 56 AIR CONDITIONED FLOOR STANDING CABINET



The Easycab range of floor standing cabinet IP56 with 1000W Air Condition is designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with GB/T 19183 and IEC 61969.

FEATURES

- Single front and end pod doors with stainless steel swing handles and three point locking
- Anti-jemmy strips fitted to doors for security
- Designed to meet IP56
- Support the installation of an aircon unit
- Peaked roof
- Removable gland plate in base of each bay
- Capable of mechanically fixing non rack mountable products to the back of the cabinet

Material	304 Stainless Steel
Deg. of Protection	IP 56
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Loading capacity	800 Kg
Material thickness	Mounting Rails: 2.0mm, Others: 1.5-2.0mm
Operation Temperature	-40°C to +55°C
Relative Humidity	Less than or equal to 95 percent (+35°C)
Atmospheric Pressure	70KPa to 106Kpa
Cooling Capacity	1000W
Voltage / Frequency	230 V ~ 50/60 Hz
Current	5.5 A @ 50 Hz, 6.5 A @ 60 Hz
Starting current	16 A Max. current: 7.9 A
Nominal power	1,17 kW @ 50 Hz, 1,41 kW @ 60 Hz
Max. power	1,65 kW @ 50 Hz, 2,1 kW @ 60 Hz
Cooling Unit Dimension	783x483x200mm
Cooling Unit Weight	32.0 Kg

IP 56 AIR CONDITIONED FLOOR STANDING CABINET

ACCESSORIES

No.	Item	800 wide	800wide	Materials	Treatment	Note
1.	Frame	2	2	2.0mm Stainless Steel	Powder coating	
2.	Front Door	1	1	1.5mm Stainless Steel	Powder coating	with file box
3.	Side Door	2	2	1.5mm Stainless Steel	Powder coating	Unremovable
4.	Back Door	1	1	1.5mm Stainless Steel	Powder coating	
5.	Lock	1	1	\	\	Handle Lock
6.	Top cover	1	1	1.5mm Stainless Steel	Powder coating	With water proof panel
7.	Door seal	1	1	Black Rubber	\	
8.	Door knob	1	1	Stainless Steel T=1.5	GE	
9.	Release fastener	\	6 or 12	Stainless Steel=1.5	Powder coating	H≤27U, 6pcs
10.	Bottom panel	1	1	Stainless Steel=1.5	Powder coating	
11.	Mounting angle	6	6	Stainless Steel=1.5	Powder coating	H≤27U, 4pcs
12.	Mounting profile	4	4	Stainless Steel=2.0	Zinc plated	
13.	Plinth	1	1	Stainless Steel=2.0	Powder coating	L=10 to 20 cm

ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
132R-158820X	15U 800 x 800 IP 56 Front Metal Door Stainless Steel Floor Standing Cabinet Air Conditioned 1000W	15	800x800x820
132R-288820X	28U 800 x 800 IP 56 Front Metal Door Stainless Steel Floor Standing Cabinet Air Conditioned 1000W	28	800x800x1400

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)