

# 8CH NETWORK VIDEO RECORDER



## ENR-02008-N-EPK

### FEATURES

- 8 Channel input
- Support Enhanced (H.265, H.264), H.265, H.264 Video Formats
- 2 SATA HDDs
- HDMI and VGA Simultaneous Output
- ONVIF Profile S
- PoE Support



### SPECIFICATION

<b>MODEL</b>	<b>Model No.</b>	<b>ENR-02008-N-EPK</b>
	<b>Type</b>	8CH NETWORK VIDEO RECORDER
<b>VIDEO &amp; AUDIO</b>	<b>Video Input</b>	8-Ch
	<b>Incoming Bandwidth</b>	80 Mbps
	<b>Outgoing Bandwidth</b>	80 Mbps
	<b>HDMI/VGA Output</b>	HDMI: 3840×2160, 1920×1080, 1280×1024, 1024×768 VGA: 1920×1080, 1280×1024, 1024×768
	<b>Audio I/O</b>	1-ch Input/ 1-ch Output
	<b>Two way Audio</b>	Supported
	<b>Multi-screen Display</b>	1/4/8/9
	<b>OSD Type</b>	Channel Name, Date
<b>DECODING</b>	<b>Video Compression</b>	Enhanced (H.265, H.264), H.265, H.264
	<b>Audio Compression</b>	G.711A/G.711U
	<b>Bit Rate Type</b>	CBR, VBR
	<b>Recording Resolution</b>	12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/D1
	<b>Recording Mode</b>	Manual, Schedule (Regular, Continuous), Event
	<b>Trigger Events</b>	Motion Detection, Video Loss, Alarm in, IVS
	<b>Decoding Capability</b>	1x12MP, 4x4MP, 8x1080P
<b>MONITORING</b>	<b>Synchronous Playback</b>	8/4/1
	<b>Live View Functions</b>	Snapshot, Record, Digital Zoom, Record, PTZ toolbar, Volume adjustment, Image Setting
	<b>Playback functions</b>	Sync playback, Play, Pause, Stop, Fast play, Slow Play, Full Screen, Backup Selection, Snapshot, Search by Date, Picture Grid
	<b>Search Mode</b>	Time/Date, Alarm, Picture grid, Event
	<b>Backup Mode</b>	USB, Network
	<b>Export Video Format</b>	MP4
	<b>Export Picture Format</b>	JPG

★Product specification and availability are subject to change without notice.

# 8CH NETWORK VIDEO RECORDER



## ENR-02008-N-EPK

MODEL	Model No.	ENR-02008-N-EPK
	Type	8CH NETWORK VIDEO RECORDER
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTSP/RTCP, PPPoE, NTP, UPnP, QoS, SMTP, IGMP, 802.1X, NFS, Unicast, Multicast, ARP, SNMP, SSL, Telnet, SFTP (SSH), P2P, 3G/4G
	Compatibility	ONVIF Profile S, SDK / CGI
	Network	2xRJ45 (10/100/1000 Mbps) Self Adaptive Ethernet Port
	Serial Interface	1xRS485
	HDMI Interface	1xHDMI
	VGA Interface	1xVGA
	USB Interface	3xUSB 2.0
	Alarm I/O	8/1
PoE	PoE Interface	8 RJ-45 (10M/100M) Self Adaptive Ethernet Port
	Max. Power for PoE Port	80W
SMART	Alarm Management	Input & Output event, Alarm I/O error, IP Conflict, Hard disk full, No hard disk, Hard disk R/W error, HDD SMART check error, Abnormal recording, Motion detection, Tampering (Masking), Smart detection, Video loss
	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Analytics	Loitering, Multi Loitering, Abandoned object (Object Left), Missing object (Object Lost), People Counting, Wrong Way Detection, Abnormal Speed, Illegal Parking *Compatible with analytic supported cameras
STORAGE	SATA	2 SATA Interfaces
	Capacity	Up to 12TB for each HDD
	eSATA	Supported
	ANR	Supported
GENERAL	Operating System	Embedded Linux
	Remote Users	8
	Client Application	EyeGuard
	Power Supply	100 ~ 240V AC
	Redundant Power	N/A
	Max. Power Consumption	≤15W (without HDD)
	Working Environment	-10°C ~ 55°C
	Working Humidity	≤90% RH
	Chassis	1 U
	Reset Button	Supported
	Dimension	372 × 310.5 × 46.5 mm
Net Weight	2.1 Kg (without HDD)	

Dimension Unit : mm



### ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-02008-N-EPK	8Ch Embedded Network Video Recorder with 2 HDD Bays Supports 8# PoE Ports, 4K Cameras, HDMI, VGA and ONVIF	1

### PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-02008-N-EPK	Carton Box	-	-

★Product specification and availability are subject to change without notice.