

NVS-IP30008PM

IP NETWORK PAGING STATION(ON-WALL TYPE)



DESCRIPTION

NVS-IP30008PM Series wall mount intelligent paging station is a network high fidelity paging station based on TCP/IP Transfer protocol, which can be attached to anywhere that the network can reach. It has the characteristics of high stability of traditional paging station, stable and reliable operation and low failure rate. Signal all-digital transmission design, intelligent control as the core. 7-inch real color LCD screen/touch screen control, graphics and image of the user interface is more human-friendly. With auxiliary input and output channels, local audio source extension and amplifier expansion can be realized. Built-in player which is independent developed by DSPPA, the implementation of host program local monitoring.

FEATURES

- ⊙ Support 100 / 10Mbps adaptive TCP / IP network transmission protocol
- ⊙ Using 7-inch true color touch screen, aluminum alloy high-grade drawing industrial panel design, hanging wall and wall embedded design
- ⊙ Using high-fidelity and hand-held dynamic microphone design
- ⊙ With multi-level level indication function, speech sound pressure more intuitive.
- ⊙ With manual shortcuts, quick and quick paging.
- ⊙ Built-in 1W monitor speakers, easy to listen to programs and intercom use
- ⊙ With 1 input (expandable external program source, wireless MIC access), 1 local line output (offline output local power amplifier paging), 1 AUX line output (extended monitoring power).
- ⊙ Graphic user-friendly design, display content more intuitive
- ⊙ Built-in high fidelity dynamic range of AGC processing circuit and high-performance DSP sound processing circuit
- ⊙ Using embedded real-time system platform and high-performance ARM processor
- ⊙ Can edit the network play terminal grouping
- ⊙ Can be selected for the network broadcast terminal paging, intercom (intercom system with) function and intelligent paging station paging and intercom between each other, (intercom system with).
- ⊙ Can play web host library songs
- ⊙ With audio log recording function, the contents of the paging real-time sound recording, and can play access.
- ⊙ With user password and rights management.

| Specifications | |
|---|---------------|
| Model | NVS-IP30008PM |
| Rated output voltage | 1.0±0.2V |
| Mic input sensitivity (output 1V) | 50±10mV |
| Mic Distortion (1KHZ/1V) | MIC: ≤0.5% |
| Mic gain limit effective frequency range (±3DB) | 200-12000Hz |
| Mic SNR (30k low-pass) | ≥65dB |
| MIC AGC starting control valve | 600±50mV |
| AUX input sensitivity (output 1V) | 300±50mV |
| AUX distortion (1kHz/1V) | AUX≤0.2% |

NVS-IP30008PM

IP NETWORK PAGING STATION(ON-WALL TYPE)

| Specifications | |
|--|--------------------|
| Model | NVS-IP30008PM |
| AUX SNR(30k low-pass) | ≥70dB |
| AUX gain limit effective frequency range (±3DB) | 35-20000Hz |
| Aux dynamic range | ≥26dB |
| Monitor (intercom voice) effective frequency range of gain limit (± 3dB) | 60-7000Hz |
| Monitor SNR (intercom voice) | ≥65dB |
| Working voltage range | AC180-240V |
| Standby power consumption | 14.5W |
| Power | AC220V (±10%)/50Hz |
| Power consumption | 22W |
| Packing dimension | 485x255x170mm |
| Device dimension | 315x178x88mm |
| Gross weight | 3Kg |
| Net weight | 2Kg |

ORDERING INFORMATION

| Part Number | Description | Standard Quantity |
|---------------|---|-------------------|
| NVS-IP30008PM | IP Network Paging Station(on-wall type) | 1 No. |

PACKING INFORMATION

| Part Number | Packing Mode | Gross Weight(kg) | Dimensions(mm) |
|---------------|--------------|------------------|----------------|
| NVS-IP30008PM | Carton Box | 3.0 | 485x255x170 |