

2X25W IP NETWORK WALL MOUNT SPEAKER



DESCRIPTION

NVS-IP30023SP is a network full digital signal processor Hi-Fi speaker based on TCP/IP protocol. With dual network interface design, it can be connect to anywhere the network reaches. Under intelligent control of the system center, this terminal serves to output the long distance audio data flow. Built in MP3 player, USB port, and SD slot, for local program playing. With 1 aux input to connect with other audio source equipments; 1 aux audio output for connection with other amplifiers for power extension; and 1 MIC input for local Paging.

FEATURES

- ⊕ 100/10Mbps, TCP/IP network transmission protocol adaptive
- ⊕ High class waterproof grille, engineering plastic mold design
- ⊕ Built-in 2*25W high efficiency digital amplifier with low power-consuming.
- ⊕ Built-in 4Ω 25W Hi-Fi speakers with high output sensitivity
- ⊕ Audio source includes: Background music, emergency call, and alarm from the Host
- ⊕ 1 auxiliary audio input, 1 auxiliary audio output and 1 microphone input
- ⊕ 100V local emergency input, easy to connect with the local fire alarming system
- ⊕ Accept infrared remote control

Specifications		
	Model	
		NVS-IP30023SP NVS-IP30024SP
AUX Input	Input Resistance	>10k Ω
	Input Sensitivity	1000 mV
	Freq Resp.	50Hz-20kHz
	Distortion	≤0.1%
	SNR	≥80 dB
MIC Input	Input Resistance	>600 Ω
	Freq Resp.	50Hz-20kHz
	Distortion	≤1%
	SNR	≥75 dB
AUX Output	Output Resistance	<50 Ω
	Output Sensitivity	1000mV
	Freq Resp.	50Hz-20kHz
	Distortion	≤0.1%
	SNR	≥75 dB


NVS-IP30023SP/NVS-IP30024SP

2x25W IP Network Wall Mount Speaker

Specifications			
	Model	NVS-IP30023SP	NVS-IP30024SP
Amplifier Output	Power	25W/4 Ω	
	Freq Resp.	50Hz-20kHz	
	Distortion	≤0.1%	
	SNR	≥80dB	
Built-in Speaker	Max SPL	≥100dB	
	Power	25W/4 Ω	
	Freq Resp.	50Hz-20kHz	
	Distortion	≤0.1%	
Interface	SNR	≥80dB	
	Dual Ethernet Interface	CAT-5J	
	AUX Input	RCA	
	AUX Output	RCA	
	MIC Input	6.3 Socket	
Digital Audio Parameter	Aux Speaker Output	3.81MM	
	Decode Format	Support PCM\MP3	
	Sampling Frequency	8k-48kHZ	
Other	Power Supply	80-250V/50Hz	
	Over-current, Over-heat, Over-voltage Protection	Yes	

DIMENSIONS

Back Panel



- | | |
|--------------------------|--|
| 1. AC220V Power Input | 2. Power On/Off |
| 3. Speaker Output(2*25w) | 4. 100V Audio Input |
| 5. Aux In | 6. Aux Out |
| 7. MIC Input | 8. Color Screen On-demand Terminal Input |
| 9. LAN Input | |

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP30023SP	2x25W IP Network Wall Mount Speaker(Black)	1 No.
NVS-IP30024SP	2x25W IP Network Wall Mount Speaker(White)	1 No.

PACKING INFORMATION

Part Number	Packing Mode	Gross Weight(kg)	Dimensions(mm)
NVS-IP30023SP	Carton Box	-	-
NVS-IP30024SP	Carton Box	-	-