

# NVS-IP30025SP/NVS-IP30026SP POE WALLMOUNT SPEAKER



## DESCRIPTION

NVS-IP30025SP/NVS-IP30026SP is a network full digital signal processor Hi-Fi speaker based on TCP/IP protocol. With dual network interface design, it can be connect to anywhere the network reaches. Under intelligent control of the system center, this terminal serves to output the long distance audio data flow. Built in MP3 player, USB port, and SD slot, for local program playing. With 1 aux input to connect with other audio source equipment; 1 aux audio output for connection with other amplifiers for power extension; and 1 MIC input for local Paging.

## FEATURES

- ⊕ 100/10Mbps, TCP/IP network transmission protocol adaptive
- ⊕ High class waterproof grille, engineering plastic mold design
- ⊕ Built-in 10W high efficiency digital amplifier with low power-consuming.
- ⊕ Audio source includes: Background music, emergency call, and alarm from the Host
- ⊕ 1 auxiliary audio input, 1 auxiliary audio output and 1 microphone input
- ⊕ 100V local emergency input, easy to connect with the local fire alarming system
- ⊕ Accept infrared remote control
- ⊕ POE power supply, easy for installation and cable laying

Specifications		
Model	NVS-IP20019PM	NVS-IP20019PM
AUX input	Input impedance	>10kΩ
	Input sensitivity	1000 mV
	Frequency response	50Hz-20kHz
	Distortion	≥0.1%
	Signal-to-noise ratio	≤80 dB
MIC input	Input impedance	>600Ω
	Frequency response	50Hz-20kHz
	Distortion	≥1%
	Signal-to-noise ratio	≤75 dB
AUX output	Output impedance	<50Ω
	Output sensitivity	1000mV
	Frequency response	50Hz-20kHz
	Distortion	≥0.1%
	Signal-to-noise ratio	≤75 dB
Power amplifier output	Power	10W/4Ω
	Frequency response	50Hz-20kHz
	Distortion	≥0.1%
	Signal-to-noise ratio	≤80dB

# NVS-IP30025SP/NVS-IP30026SP

## POE WALLMOUNT SPEAKER

Specifications			
Model		NVS-IP20019PM	NVS-IP20019PM
Built-in amplifier	Digital amplifier	1x10W	
Built-in speaker	Maximum sound pressure level	≤100dB	
	Power	10W/4Ω	
	Frequency response	50Hz-20kHz	
	Distortion	≥0.1%	
	Signal-to-noise ratio	≤80dB	
Interface	Dual Ethernet interface	CAT-5	
	AUX input	RCA jack	
	AUX output	RCA jack	
	MIC input	6.3 Socket	
	Auxiliary speaker output	3.81MM Phoenix socket	
Digital audio parameters	Decoding format	Support PCM\MP3 format	
	Sampling rate	8k-48kHz	
	Package size	590×275×390mm	
	Machine size	310×215×200mm	
	Net weight	4.2kg	

### ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP30025SP	POE Wall Mount Speaker 10W (Black)	1 No.
NVS-IP30026SP	POE Wall Mount Speaker 10W(White)	1 No.

### PACKING INFORMATION

Part Number	Packing Mode	Gross Weight(kg)	Dimensions(mm)
NVS-IP30025SP	Carton Box	4.2	590×275×390
NVS-IP30026SP	Carton Box	4.2	590×275×390