

NVS-IP20002NS

IP NETWORK SERVER (2U)



DESCRIPTION

The IP Broadcast Intercom Server adopts industrial host. The system is stable and reliable with SSD and aluminum alloy panel. Working 24 hours a day, it can operate stably in low and high temperature for a long time. With Ethernet hardware, additional line maintenance is not required for the whole system. It has high performance, low power consumption and can run steadily for a long time. With professional server software, it can configure, manage and maintain all terminal devices.

FEATURES

- ◆ 10/100M self-adaption, support DHCP/IP settings, LAN and WAN.
- ◆ Professional rack case design and aluminium alloy structure, with high anti-magnetic, anti-dust, anti-impact ability.
- ◆ Built-in professional IP broadcast management software, support timing management, built-in program management and zone management.
- ◆ Can configure multiple USB and VGA interfaces, which is convenient and fast.

Specifications	
Model	NVS-AC10001VC
CPU	Intel® Core™ I5 4430 3.0GHz
RAM	4G/DDR3
Hard disk	120G SSD
Video interface	HDMI, VGA
USB	Front: USB×2, Rear: USB×4
Support protocols	TCP/IP, UDP, ICMP, IGMP (Multicast)
Network	RTL8111F Gigabit Network Card Chip, WOL/PXE
Power input	ATX Wide Voltage Power Supply (AC 127-240V /47-63Hz/7/3.5A)
Temperature & Humidity	-10°C~50°C, ≤90%RH (No condensation)
Dimension	88×490×335mm
Weight	5.9kg

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP20002NS	IP Network Server(2U)	1 No.

PACKING INFORMATION

Part Number	Packing Mode	Weight (Kg)	Dimensions(mm)
NVS-IP20002NS	Carton Box	5.9	88×490×335