

PA Power Amplifier 2000W



DESCRIPTION

The NVS-20182001AM is a public address Power Amplifier with rack mount design in 3U type and rated power is 2000W. For each channel, balanced and unbalanced inputs are available. Balanced line output feeds to another power amplifier as well as secures the signal transmission is less noise and longer distance. When choosing different speaker matchings, 70V, 100V, and 4-16 Ω speaker outputs are convenient for installation. There is a master volume control available. Complete protection includes overload, high temperature, short circuit, and clip. Equipped with indications for power, signal, clip, protection and temp. It is an ideal choice for commercial and industrial public address applications.

FEATURES

- Rack mount amplifier in 3U height
- Isolated transformer for human safety operation
- Indications for power, signal, clip, protection and temp
- Reliable protection from overheat, overload, clip & short circuit
- \odot XLR socket and 6.35mm jack for mixer or amplifier link
- Device of radiator cooling fan ensures working effectively
- \odot 100V, 200V and 4-16 Ω speaker outputs
- Rated power 2000W, 5 LED indicator for status display

| Specifications | | |
|---------------------------|----------------------|--|
| Model | NVS-20182001AM | |
| Rated Power | 2000W | |
| Frequency Response | 80Hz~15kHz (±3dB) | |
| Input Sensitivity | OdBv | |
| Total Harmonic Distortion | <0.3% into 4Ω/1kHz | |
| Signal to Noise Ratio | > 85dB | |
| Rated Output Voltage | 89.5V/100V/200V | |
| Damping Factor | 200:1 | |
| Input CMRR | >90dB | |
| Power Requirement | AC220~240V / 50~60Hz | |
| Weight | 36 Kg | |
| Dimension | 484x480x132mm | |

ORDERING INFORMATION

| Part Number | Description | Standard Quantity |
|----------------|--------------------------|-------------------|
| NVS-20182001AM | PA Power Amplifier 2000W | 01 |