

NVS-IP20019PM SIP Phone



DESCRIPTION

The new IP telephone, with advanced design and cost-effective price, greatly improves the production efficiency of enterprises

FEATURES

- ⊙ Simple and fashionable appearance.
- ⊙ Cost-effective price and green environment protection concept
- ⊙ Simple installation and configuration
- ⊙ Support 100 Mbps Ethernet - adaptive 10/100 Mbps network port, with high-speed transmission
- ⊙ High Compatibility - Compatible with SIP-based IP PBX/Softswitch/IMS platforms, such as Asterisk, Broadsoft, 3CX, Elastix, Zycoo, etc.
- ⊙ Full duplex hands-free calls, supports Acoustic Echo Cancellation (AEC) with maximum 96ms echo tail length cancellation

Specifications	
Model	NVS-IP20019PM
Number of SIP Lines	2
Phone book Memory	Up to 500 records
Call history	up to 300
Protocols	SIP2.0 over UDP/TCP/TLS, RTP/RTCP/SRTP, STUN
Network	10/100Mbps Ethernet (Bridging pattern)
Virtual Private Network (VPN)	L2TP (Basic, Unencrypted) /OpenVPN
Display	128 x 48 lattice screen with backlight
Main Chip	Broadcom
Connection Interface	RJ9 Phone Interface x2: Handle x1, Headphone x1
Dynamic adaptive jitter buffer	up to 300 ms
Narrow band coding	G.711a/u, G.723.1, G.726-32K, G.729AB
Installation	Table Top, Vertical
Power consumption	standby - 0.89W~1.2W, peak - 1.81W ~2.5W
Relative humidity	10 ~ 65%
Working temperature	0 ~ 40 °C
Input power supply	5V/ 0.6A
Working ambient temp.	-20°C Up to +55°C
Product dimension	250 x 205 x 66 mm

NVS-IP20019PM
SIP Phone



ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP20019PM	10.1" Network Touch Screen Paging Station	1 No.

PACKING INFORMATION

Part Number	Packing Mode	Gross Weight (kg)	Dimensions (mm)
NVS-IP20019PM	Carton Box		250x205x66

SIP Phone