JUNCTION BOX FOR EXPLOSION PROOF CAMERA



ENB-BZAFJ68

FEATURES

304/316L Stainless Steel Construction
Fiber Converting Module Support
Junction Box for Explosion Proof Camera
IP68



SPECIFICATION

DEL	Model No.	ENB-BZAFJ68	
MODEL	Туре	JUNCTION BOX FOR EXPLOSION PROOF CAMERA	
	Construction	304/316L Stainless Steel	
	Cable Thread Hole	4pcs: M25*1.5, M27*1.25 (Optional 6pcs)	
	Ingress Protection	IP68	
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port	
	Fiber Port	1 Port-Single Mode Single Fiber (Optional Multi Mode Sigle Fiber)	
	Fiber Port Type	SC (Standard) / ST / FC	
	Transmit Distance	Single Mode: 20 km (Standard) / 40 km / 80 km Multi Mode: $< 5 \text{ km}$	
	Voltage & Power	DC 9-24V &≤3 W	
7	Working Temperature	-45 ~ 85 °C	
GENERAL	Working Humidity	≤95% RH (non-condensing)	
H	Atmospheric pressure	80 kPa ~ 110 kPa	
G	Surge Protection	Supported (Optional)	
	Fit Zone	Gas Zone 1, 2 (IIA, IIB, IIC, T1-T6) Dust zone 21, 22	
	Overall Dimensions	413x397x183 mm (with Ex cable glands)	
	Inner Size	φ 230x120 mm	
	Weight	16.8 Kg (4 entries) 18.2 Kg (6 entries)	

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENB-BZAFJ68	IP68 Rated SS304 (316L optional) Explosion Proof Junction Box with Fiber Converting Module	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENB-BZAFJ68	Carton Box	-	-