

2MP FIXED COMPACT DOME CAMERA



ENC-HCD5F-30R-91

FEATURES

2.8 mm Fixed Lens
Smart IR upto 30 m
ONVIF Profile (S, G, T)
Built-in Mic
PoE, IP67



SPECIFICATION

MODEL	Model No.	ENC-HCD5F-30R-91
	Type	2MP FIXED COMPACT DOME CAMERA
CAMERA	Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
	Day/Night	IR Cut Filter with Auto Switch
	Lens Type	Fixed
	Focal Length	2.8 mm
	Digital Zoom	16
	Iris	Fixed
	Lens Mount	M12
	Angle of View (H)	104.9°
	Angle of View (V)	56.5°
	Angle of View (D)	119.2°
	Angle Adjustment	Pan 0~340°, Tilt 0~75°, Rotate 0~360°
	Aperture	F1.6
	Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F1.6 , B/W: 0 lux with IR
	AGC	Auto / Manual
	Digital Noise Reduction	3D DNR
	S/N Ratio	≥60 dB
	Defog	Smart Defog
WDR	120 dB	
Smart IR	Up to 30 m	
Wavelength	850 nm	
White LEDs	2	
Illumination Distance	15 m	

★Product specification and availability are subject to change without notice.

2MP FIXED COMPACT DOME CAMERA



ENC-HCD5F-30R-91

MODEL	Model No.	ENC-HCD5F-30R-91
	Type	2MP FIXED COMPACT DOME CAMERA
DORI	Lens	2.8 mm
	Detection	38.6 m
	Observation	15.3 m
	Recognition	7.7 m
	Identification	3.8 m
VIDEO	Max.Resolution	1920x1080
	Video Compression	Enhanced (H.265, H.264), H.265, H.264
	Frame Rate	Main Stream: (1920x1080, 1280x720, 704x480, 640x480) @ 30fps, (1920x1080, 1280x720, 704x576, 640x480) @ 25fps Sub Stream: (704x480, 704x240, 640x360, 352x240) @ 30fps, (704x576, 704x288, 640x360, 352x288) @ 25fps
	Stream Settings	I-Frame, PAL/NTSC, Frame Rate (1~30FPS), SVC
	Video Bit Rate	32 Kbps~6 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Hue, Sharpness, Rotation/Mirror, Gain, Exposure, Day/Night
	White Balance	Auto, Semi Auto, Sunshine, Daylight, Warm Light, Filament, Nature Light, Lock WB, Manual
	Corridor Mode	N/A
	HLC	Supported
	BLC	Supported
	OSD	Up to 3 Regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes (16x16, 32x32, 48x48)
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711A, G.711U, ADPCM_LD
	Audio Bit Rate	8 kbps, 32 kbps, 48 kbps
	Audio I/O	N/A
	Built-in Mic	Supported with noise cancellation
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire)
	Intelligent Identification	N/A
	Statistical Analysis	N/A
	Alarm Management	Motion Detection, Tampering (Masking), IP Address Conflict
	Alarm Notification	E-mail (Notification and Snapshot), HTTP (Alarm Icon), FTP (Snapshot and Recording), SD Card (Recording)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, ICMP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, FTP, NTP, UPnP, Telnet, P2P
	Security	AES Video Encryption, IP Filter, User Authentication (Multiple Privilege Level)
	Compatibility	ONVIF Profile (S, G, T), SDK/CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	N/A
	Edge Storage	Micro SD card slot, up to 512 GB
	ANR	Supported
	Cable Interface	Pig Tail
	Remote Connection	≤2
	Max. Users	32
	Client Application	EyeConnect
Web Language	15	
GENERAL	Power Supply	DC 12V, PoE (802.3af)
	Max. Power Consumption	≤6 W (12V DC), ≤8 W (PoE)
	Working Temperature	-40 °C ~ 65 °C
	Working Humidity	≤95% RH (non-condensing)
	Ingress Protection	IP67
	Vandal Resistant	N/A
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	116.6x83.7 mm
Net Weight	0.47kg	


★Product specification and availability are subject to change without notice.

2MP FIXED COMPACT DOME CAMERA



ENC-HCD5F-30R-91

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HCD5F-30R-91	2MP Starlight IR IP H.265 Compact Dome Camera with 2.8mm Fixed Lens, PoE, SD Card Slot, Built-in Mic, 30m IR and 15m Warm Light Support	1
ENB-BTEW65	Wall Mount for Norden Lite Series Turret Camera, Mini Dome (Plastic)	1
ENB-BTEJ67	Junction Box for Norden Fixed Lens Turret Camera and Fixed Lens Mini Bullet Camera	1
ENB-BTDV66	Pole Mount Bracket for Norden Dome Camera	1
ENB-BTDH66	Outer Corner Bracket for Norden Dome Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HCD5F-30R-91	Carton Box	-	-