



NORDEN Power Distribution Units are designed and manufactured in a modularized way exclusively for cabinets. The product is equipped with supply socket modules meeting different systems and standards in the world. The series products can be produced accordingly to customers' special requirements.

COMPLIANCE

EN 55032: 2015
 EN 61000-3-12: 2011
 EN 61000-3-11: 2000
 EN 55035:2017, RoHS
 BS EN50288-7

DESIGN & MATERIALS

| | |
|----------------------------|--|
| Material of Construction | PC/ABS alloy, High Impact flame retardant thermoplastic –UL94-V0 |
| Shell Material & Colour | Aluminium, black |
| Outlet Qty. | 18 way |
| Plug Type | IEC320 C20 16A plug |
| Power Input Style | Left-end single input |
| Bracket Installation Style | Frontal Installation Style |
| Control function | Switch |
| Lead length | 3m |

ELECTRICAL & ENVIRONMENTAL DATA

| | |
|-----------------------------------|----------------|
| Current Rating | 16A |
| Maximum load current available in | 16Amp |
| Input frequency | 50 or 60 Hz |
| Maximum load capacity | 4KW |
| Operating Environment | 0-55°C |
| Operating Relative Humidity | 5% – 95 % |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -20°C to +70°C |
| Storage Elevation | 0-3000 meters |

ORDERING INFORMATION

| Part Number | Description |
|------------------|--|
| 159X-218A12C062X | 18 Way [12 X C13 + 6 X CEE 7/3] , 16 A, Master Switch , IEC320 C20 Plug PDU, 3 Meter cable length vertical Installation. |