

IR ILLUMINATOR



ENI-TTA008-045R

FEATURES

30W IR Illuminator
8 LED Panels
45m Distance Support
IP66



SPECIFICATION

MODEL	Model No.	ENI-TTA008-045R
	Type	IR ILLUMINATOR
GENERAL	Beam Angle	8°
	Beam Distance	45m
	Distance for LPR	22 ~ 45m
	Flash Trigger Method	Triggered in Sync with Global Shutter Camera
	Synchronization Port	Support
	Response Time	Real Time
	IR	Support
	LED	YES
	Wavelength	850nm
	Power Supply	48V
	Power Consumption	25 ~ 30W
	Working Temperature	Up to 60 °C
	Working Humidity	90% RH (non condensing)
	Ingress Protection	IP66
Surge Protection	Support	
Material	Aluminum Die-Cast	
Panel	8 LED Panel	
Dimensions	430x360x200 mm (without clamp)	
Net Weight	-	
INSTALLATION	Power	The Power and LED Panel Wires must be Oriented Downward to Prevent Water Intrusion.
	Earthing	Lighting Safety Precautions must be Taken and Power Wires must be Grounded.
	Settings	Gently Modify the Bolt of Brightness, Sensor and Time.
	Installation	Professional Electricians or Quality Technicians Should Install and Adjust.
	Caution	Do Not Open the Case and Remove the Power Supply

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENI-TTA008-045R	IR illuminator with 8° Beam Angle, 45m IR and IP66 Support.	1

IR ILLUMINATOR



ENI-TTA008-045R