

# INTELLIGENT TRAFFIC STROBE LAMP



## ENI-TTA013-045W

### FEATURES

8 LED Panels
30W IR Illuminator
45m Distance Support
IP66



### SPECIFICATION

MODEL	Model No.	ENI-TTA013-045W
	Type	INTELLIGENT TRAFFIC STROBE LAMP
GENERAL	Beam Angle	13°
	Beam Distance	45m
	Best Distance for LPR	22 ~ 45m
	Flash Trigger Method	Triggered in Sync with Global Shutter Camera
	Response Time	Real Time
	Color	White LED
	Wavelength	850 nm
	Power Supply	48V
	Power Consumption	25 ~ 30W
	Working Temperature	up to 60 °C
	Working Humidity	≤90% RH (non condensing)
	Ingress Protection	IP66
	Surge Protection	Support
Material	Aluminum Die-Cast	
Panel	8 LED Panel	
Dimensions	430x360x200 mm (without clamp)	
Net Weight	-	
INSTALLATION	Power	The Power and LED Panel Wires Must be Oriented Downward to Prevent Water Intrusion.
	Earthing	Lighting Safety Precautions Must be Taken and Power Wires must be Grounded.
	Settings	Gently Modify the Bolt of Brightness, Sensor and Time.
	Installation	Professional Electricians or Quality Technicians Should Install and Adjust.
	Caution	Do Not Open the Case and Remove the Power Supply.

# INTELLIGENT TRAFFIC STROBE LAMP



**ENI-TTA013-045W**

MODEL	Model No.	ENI-TTA013-045W
	Type	INTELLIGENT TRAFFIC STROBE LAMP

## ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENI-TTA013-045W	Strobe illuminator with 13° Beam Angle, 45m White Light and IP66 Support.	1

## PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENI-TTA013-045W	Carton Box	-	-